



## 2500Meters Thrower-XSWORD L2K

### Features

- Adopts newest focus beam source
- Max output 500lm
- Max beam distance 2500 meters
- Powered by two 18650 rechargeable Li-ion batteries
- 245mm(length) \* 60mm(head \* 25.4mm(body)
- Weight - 285g
- Constant current offers stable output
- Reverse polarity protection
- Memory function
- Anti-slide and wicking design
- Backward switch, three brightness levels
- Made from solid aluminum stick
- Mil-spec Type III hard anodized finish
- Aspheric surface lens with coating at double sides
- Tactical grip ring
- IPX-8 (waterproof up to two meters)

### Technical Parameters

ANSI/NEMA F11	HIGH	MID	LOW
Light Output	500Lumens	300 Lumens	100 Lumens
Runtime	2h	3h20min	12h
Beam Distance	2500m		
Impact Resistance	1.5m		
Waterproof	IPX-8:Waterproof up to two meters!		
Specifications	245mm*60mm*25.4mm		

Above referential results are tested by using 2pcs 18650 Li-ion battery (3.7V/3500mAh). The result may vary when adopting different batteries or in different environment.

### Operation Instruction

#### Tap-on switch

Tap and hold for momentary-on  
Slightly tap the switch continuously to cycle through High-Med-Low

#### Turn on/off the light

Select a working mode by slightly tap the switch. Fully press the switch to turn on the light.

#### Intelligent Memory Circuit

The torch remembers working mode after staying the mode for more than 4 seconds.

### Battery Replacement

Take off the tail cap. Then insert 2pcs of 18650 battery with the positive terminal towards the head. After loading the batteries, screw the tail cap on with all of the threads in proper alignment.

### Warning

Please note: DO NOT look into the beam or point into any person or animals eyes. Keep out of reach of Children.

### Usage and Maintenance

- Disassembling the sealed head can cause damage to the light and will void the warranty.
- High quality battery is recommended. If the light will not be used for an extended period, remove the battery, or the light could be damaged by electrolyte leakage or battery explosion.
- Long-term use can result in O-ring wear. To maintain a proper water seal, replace the ring with an approved spare.
- When the head part or tail cap can't be turned smoothly, apply silicone grease on threads please.

### Optional Accessories

MAXTOCH offers various accessories to meet different requirements. You could learn more from our online store <https://maxtoch.aliexpress.com>

### Warranty

1 year warranty -MAXTOCH offers free warranty work if the problem is caused by normal usage within 1 years after receipt.

Lifetime warranty- For the life of your light, repairs will be made with no labor chargers and as long as parts are available from MAXTOCH. You will be charged for the parts needed to repair your light.

Following situations are excluded from warranty

- Damage caused by improper disassembly, modification and improper usage is excluded from warranty.
- Battery is excluded from warranty. If the battery doesn't work upon receipt, it could be replaced.
- Accessories come along with flashlight such as lanyards, bag, o-ring, etc.. are not covered by the warranty.

For the latest information on MAXTOCH® products and services, please send an email to [service@maxtoch.cn](mailto:service@maxtoch.cn).

All images, text and statements specified herein this user manual are for reference purpose only. Should any discrepancy occurs between this manual and information specified on [www.MAXTOCH.com](http://www.MAXTOCH.com), EST Group Co., Ltd reserves the rights to interpret and amend the content of this document at any time without prior notice.

EST Group Co., Ltd.  
Tel- +86-571-81022450  
Email- [service@maxtoch.cn](mailto:service@maxtoch.cn)  
Website- [www.maxtoch.com](http://www.maxtoch.com)